KIOTI

CS2610 SERIES

ROPS

THE BEST VALUE TRACTOR FOR SMALL ACREAGE.

Daedong Industrial Company in South Korea has won plaudits in the subcompact tractor market with the versatile KIOTI CS2610 tractor. With the increasing number of subdivisions across Australia this is the perfect tractor for home owners with property sizes of up to 5 acres or more.

The ergonomically designed operator station places operator controls within easy reach to enjoy a comfortable and smooth ride. A retractable seat belt and operator presence switch are included for safety, while access on and off is obstruction free . The dashboard illuminates when the engine is started. The digital gauge package includes tachometer, fuel and temperature gauges, along with low fuel and high temperature warning lights

Whether it is for mowing, digging, grading driveways or moving materials with the standard 4-in-1 loader, this subcompact tractor will save you hours of labour, reliably and safely. With its clever design, logically located controls and adjustable seat, operators will find the CS2610 a joy when tackling the next project.

The Kioti CS2610 feels great to drive on flat or undulating terrain.

CS2610 ROPS
25HP

CS2610 SUB COMPACT ROPS

ENGINE
- Daedong 3C100LHW-E2
- Liquid Cooled 3 Cylinder Diesel
- 1007cc Displacement
- 25 HP @ 3200 rpm
- 25.5 Litre Fuel Tank Capacity

TRANSMISSION
- 2 Range Hydrostatic Drive
- Standard Differential Lock
- 4 Wheel Drive

HYDRAULICS & LINKAGE
- Gear Pump Hydraulic System
- 24.6 lpm Max. Flow Pump Capacity
- Category 1 Three Point Linkage
- 318kg Max. Lift Capacity @ 610mm Rear of Hitch
- Position Lift Control System
- Hydraulic Power Steering

POWER TAKE OFF
- Manual Independent PTO
- 540 rpm Rear PTO Standard
- 2,200 rpm Mid PTO Standard

BRAKES
- Wet Disc Type

OPERATOR ENVIRONMENT
- Ergonomic Operator Station
- Illuminated Instrument Panel
- 12 Volt Power Outlet
- High Back Seat
- Step Through Platform
- Front Work Lights
- Easy Access Engine Bay

TRAVEL SPEEDS
- Forward 0 - 16.6 kph
- Reverse 0 - 11.2 kph

DIMENSIONS

Overall Length (inc 3PL)
2523mm

Overall Height
2226mm

Overall Width (min tread)
1400mm

Wheelbase
1400mm

Min. Ground Clearance
162mm

Weight
690kg

TYRES

Industrial Front
18 x 8.5 — 10

Industrial Rear
26 x 12.00 - 12

OPTIONAL EQUIPMENT

MOWER DECK

BACKHOE

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS

SCAN TO LEARN MORE