UNLEASH
PRECISION
AND POWER
WITH KIOTI
ZERO-TURN
MOWERS.
KIOTI
KIOTI

ZXD DIESEL

The Kioti ZXD Diesel Series is set to pleasantly surprise and delight Kioti enthusiasts, blending the familiar components they adore with the added power of diesel. Equipped with a robust 1.2L Kioti diesel engine and direct drive transaxles, this machine operates seamlessly without relying on a drive belt.

Customers can select from either a 61- or 72-inch deck, both featuring a rugged frame, a shaft-driven reinforced 7-gauge fabricated steel deck, and semi-pneumatic front casters for superior durability. Furthermore, it offers unparalleled operator comfort with a premium rubber-isolated 3-inch suspension seat and an articulating front axle, ensuring reduced fatigue and a more enjoyable mowing experience throughout the day.

Elevate your outdoor experience today with our cutting-edge zero-turn mowers.

WARRANTY
24 months Unlimited Hours
48 months 1500 hours Powertrain Warranty

THE ZERO-TURN YOU HAVE BEEN WAITING FOR.

PHONE 1800 186 866

@kiotiaustralia @kiotitractorsaustralia kioti.com.au

SPECIFICATIONS

MODEL	ZXD61	ZXD72
ENGINE		
Type	KIOTI 1.2L 3 Cyl Diesel	KIOTI 1.2L 3 Cyl Diesel
Engine Gross hp (kW)	24.5 (18.3)	24.5 (18.3)
Displacement cu. in. (cc)	72.2 (1,233)	72.2 (1,233)
Fuel Tank Capacity gal. (l)	17.1 (65)	17.1 (65)
Fuel Requirement	Diesel	Diesel
DRIVE TRAIN		
Model	KIOTI Drive Motors	KIOTI Drive Motors
Displacement (Pump/Motor) cc	23cc/23cc 11cc charge pump	23cc/23cc 11cc charge pump
Clutch ft.-lb.	Independent Wet Disc	Independent Wet Disc
TYRE SIZE		
Front	15x6.5-8 Semi-Pneumatic	15x6.5-8 Semi-Pneumatic
Rear	26x12-16 Turf Tyre	26x12-16 Turf Tyre
TRAVELING SPEEDS		
Forward mph (km/h)	11 (17.7)	11 (17.7)
Reverse mph (km/h)	7.1 (11.5)	7.1 (11.5)
Parking Brake	Foot Pedal	Foot Pedal
DIMENSIONS		
Overall Length (mm)	2,258	2,328
Overall Width (mm)	1,515	1,515
Overall Height (mm)	2,092	2,092
Wheelbase (mm)	1,441	1,510
Width (Tyre to Tyre) (mm)	1,515	1,515
Approximate Curb Weight (kg)	875	898
MOWER DECK		
Mower Deck Type	Fabricated	Fabricated
Lift Mechanism	Pedal Operated Hydraulic	Pedal Operated Hydraulic
Deck Steel Thickness	7-gauge	7-gauge
Anti-Scalp Ball Rollers	6 (4 front, 2 rear)	6 (4 front, 2 rear)
Cutting Width of Mower in. (mm)	61 (1,550)	72 (1,829)
Blades	Notched	Notched
Cutting Height in. (mm)	1-5 (25-127)	1-5 (25-127)
Discharge Chute	Side (Durable Plastic)	Side (Durable Plastic)
Deck Height Adjustment	1/4" by Dial	1/4" by Dial