KIOTI

PX1052 SERIES
CAB

WHEN YOU NEED POWER, PRECISION & PERFORMANCE.

The innovative and highly regarded PX range with a weight of 4 tonnes is designed for serious farming and is the ideal tractor for front end loader work. With a large 120 litre fuel tank and a fuel efficient engine, the PX1052 can keep on working for a long time between fuel breaks. Equipped with hydrostatic power steering, it provides smooth responsive steering that requires minimal operator effort and is ideal for loader work.

The spacious cab is designed for maximum operator comfort, featuring climate control, ergonomic seating, and intuitive controls, all aimed at reducing fatigue during long working hours.

With a focus on durability and ease of maintenance, the Kioti PX1052 cab tractor is an excellent choice for professional farmers seeking reliable and high-performing equipment for their agricultural needs.

PX1052 CAB
105HP

PX1052 CAB

ENGINE
- Perkins 1104C-44TTG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 105 HP @ 2400 rpm
- 120 Litre Fuel Tank Capacity
- Dual Air Cleaner

TRANSMISSION
- Synchro Mesh
- Power Shuttle
- Push Button Hand Clutch
- Wet Multi Disc Clutch
- 32F x 32R Speed with Hydraulic High/Low
- Rear Differential Lock

HYDRAULICS & LINKAGE
- Main Pump Capacity - 48.4lpm
- Steering Pump Capacity - 30.8lpm
- Total Maximum Flow - 79.2lpm
- 2400kgs Maximum Rear Linkage Lift Capacity
- Power Steering
- Category 2 Three Point Linkage
- Position, Draft, Mixed Control Lift System
- 4 Rear Remote Outlets
- Clevis Type Rear Draw Bar

POWER TAKE OFF
- Independent 540 / 1000 rpm PTO
- Auto PTO

BRAKES
- Wet Multi Disc Type

OPERATOR ENVIRONMENT
- High Quality Fully Adjustable Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN
- Deluxe Cabin with A/C and Heating
- Radio
- Front and Rear Wipers
- Internal / External Air Exchanger Filters
- 12v Refrigerator

TRAVEL SPEEDS
- Forward 0.82 - 38.36 kph
- Reverse 0.80 - 37.33 kph

DIMENSIONS

Overall Length (inc 3PL)
4120mm

Overall Height
2770mm

Overall Width (min Tread)
2200mm

Wheelbase
2305mm

Ground Clearance (Min)
495mm

Weight
3630kg

TYRES
AG Radial Tyres Front
340 / 85R24

AG Radial Tyres Rear
460 / 85R34

OPTIONAL EQUIPMENT

BALE SPIKE

PALLET FORK

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

RE-ORDER #KI-KB020

DEALER DETAILS

SCAN TO LEARN MORE